

CETOP 3/NG06

STANDARD SPOOLS	CAP. I • 10
AD3E...	CAP. I • 11
AD3E...J*	CAP. I • 12
AD3E...KJ	CAP. I • 13
AD3V...	CAP. I • 14
AD3L...	CAP. I • 15
OTHER OPERATOR	CAP. I • 16
AD3P...	CAP. I • 17
AD3O...	CAP. I • 17
AD3M...	CAP. I • 18
AD3D...	CAP. I • 18
"D15" DC COILS	CAP. I • 19
"B14" AC SOLENOIDS	CAP. I • 19
STANDARD CONNECTORS	CAP. I • 20
"LE" VARIANTS	CAP. I • 21
L.V.D.T.	CAP. I • 22

DIRECTIONAL CONTROL VALVES CETOP 3/NG6

INTRODUCTION

The directional control valves NG6 are designed for subplate mounting with an interface in accordance with UNI ISO 4401 - 03 - 02 - 0 - 94 standard (ex CETOP R 35 H 4.2-4-03), and can be used in all fields on account of their high flow rate and pressure capacities combined with compact overall dimensions.

The use of solenoids with wet armatures allows a very practical, safe construction completely dispensing with dynamic seals; the solenoid tube is screwed directly onto the valve chest whilst the coil is kept in position by means of a lock nut.

The special, precise construction of the ports and the improvement of the spools enables relatively high flow rates to be accommodated with a minimal pressure drop (Δp).

The operation of the directional valves may be electrical, pneumatic, oleodynamic, mechanical or lever.

The centre position is obtained by means of calibrated length springs which reposition the spool in the centre or end of travel position once the action of the impulse is over.

The solenoids are constructed with a protection class of IP66 to DIN 40050 standards and are available in either AC or DC form in different voltage and frequencies.


The new type DC coil "D15", of cause their high performance, allows to increasing the limits of use respect to last series.

All types of electrical control are available, on request, with different types of manual emergency controls.

The solenoid coils are normally arranged for DIN 43650 ISO 4400 type connectors; is available on request these variant coils: with AMP Junior connections, with AMP junior and integrated diode, with Deutsch DT04-2P connections or solenoid with flying leads. Connectors with built in rectifiers or pilot lights are also available.

The valves are designed for use with DIN 51524 standard hydraulic mineral oils and it is recommended that filters should be fitted to ensure a maximum contamination level of class 10 in accordance with NAS 1638, $\beta_{25} \geq 75$.

PRESSURE DROPS



The diagram at the side shows the pressure drop curves for spools during normal usage. The fluid used is a mineral oil with a viscosity of 46 mm²/s at 40°C; the tests have been carried out at a fluid temperature of 40°C. For higher flow rates than those in the diagram, the losses will be those expressed by the following formula:

$$\Delta p_1 = \Delta p \times (Q_1/Q)^2$$

where Δp will be the value for the losses for a specific flow rate Q which can be obtained from the diagram, Δp_1 will be the value of the losses for the flow rate Q_1 that is used.

Spool type	Connections				
	P→A	P→B	A→T	B→T	P→T
01	5	5	5	5	
02	7	7	7	7	6
03	5	5	6	6	
04	2	2	2	2	4
44	1	1	2	2	3
05	7	7	5	5	
06	5	5	7	5	
66	5	5	5	7	
07		2	6		
08	6	6			
09		5		5	

Curve No.

Spool type	Connections				
	P→A	P→B	A→T	B→T	P→T
10	5	5	5	5	
11	5			5	
22		5	5		
12		5		6	
13		5	6	6	
14	4	3	3	3	4
28	3	4	3	3	4
15-19*	5	5	6	6	
16	5	5	4	4	
17-21*	3	4			
20*	4	4	4	4	

Curve No.

(*) Value with energized solenoid

DIRECTIONAL CONTROL VALVES CETOP 3/NG6

ORDERING CODE

AD	Directional valve
3	CETOP 3/NG6
E	Type of operator For other operator see next pages
**	Spool see page Cap. I • 10
*	Mounting type (table 1)
*	Voltage (table 2)
**	Variants (table 3)
*	Serial No.
	3 = Standard
	4 = Only for RS - R6 - KJ - 7J variants

TAB.2 - VOLTAGE

AC SOLENOID B14 **	
A	24V/50-60 Hz
B	48V/50-60 Hz
J	115V/50Hz - 120V/60Hz
Y	230V/50Hz - 240V/60Hz
K	AC without coils
Other voltages available on request.	
DC COIL D15 (30W) **	
L	12V
M	24V
V	28V*
N	48V*
Z	102V*
P	110V*
X	205V*
W	DC without coils

115Vac/50Hz
120Vac/60Hz
with rectifier

230Vac/50Hz
240Vac/60Hz
with rectifier

Voltage codes are not stamped on the plate, their are readable on the coils.

TAB.1- MOUNTING

STANDARD	
C	
D	
E	
F	
SPECIALS (WITH PRICE INCREASING)	
G	
H	
I	
L	
M	

• AMP Junior coils (with or without diode) and coils with flying leads and coils type Deutsch, are available in 12V or 24V DC voltage only.

• The coil with eCoat protection (RS variant) is available in 12V, 24V, 28V or 110V DC voltage only.

* Special voltage

** Technical data see page Cap. I • 19

• **Mounting type D** is only for valves with detent

• In case of **mounting D** with detent a maximum supply time of 2 sec is needed (only for AC coils).

TAB.3 - VARIANTS

VARIANT	CODE	◆	PAGE
No variant (without connectors)	S1(*)		
Viton	SV (*)		
Emergency control lever for directional control valves type ADC3 and AD3E	LE-LF-AX-CE(*)	◆	Cap. I • 21
Emergency button	ES(*)		Cap. I • 19
Rotary emergency button	P2(*)		Cap. I • 19
Rotary emergency button (180°)	R5(*)		Cap. I • 19
Preset for microswitch (E/F/G/H mounting only) (see below note ◆)	M1(*)	◆	Cap. I • 11 - Cap. I • 15
5 micron clearance	SQ(*)	◆	
Spool movement speed control (only VDC) with ø 0.3 mm orifice	3S(*)	◆	Cap. I • 12
Spool movement speed control (only VDC) with ø 0.4 mm orifice	JS(*)	◆	Cap. I • 12
Spool movement speed control (only VDC) with ø 0.5 mm orifice	5S(*)	◆	Cap. I • 12
Spool movement speed control (only VDC) with ø 0.6 mm orifice	6S(*)	◆	Cap. I • 12
AMP Junior coil - for 12V or 24V DC voltage only	AJ(*)		Cap. I • 19
AMP Junior coil and integrated diode - for 12V or 24V DC voltage only	AD(*)		Cap. I • 19
Coil with flying leads (175 mm) - for 12V or 24V DC voltage only	SL		Cap. I • 19
Hirschmann coil eCoat surface treatment - for 12V, 24V, 28V or 110V DC voltage only	RS(*)		Cap. I • 19
Deutsch DT04-2P connection eCoat surface treatment - for 12V, 24V DC voltage only	R6		Cap. I • 19
High corrosion resistance valve - Hirschmann connector	KJ		Cap. I • 13
High corrosion resistance valve - Deutsch DT04-2P connector - for 12V, 24V DC voltage only	7J		Cap. I • 13
Deutsch DT04-2P coil - for 12V or 24V DC voltage only	CZ		Cap. I • 19

Other variants available on request.

◆ = Maximum counter-pressure on T port: 8 bar - Microswitch type MK code 1319098 must be ordered separately.

◆ = Variant codes stamped on the plate

(*) Coils with Hirschmann and AMP Junior connection supplied without connectors. The connectors can be ordered separately, Cap. I • 20.

TWO SOLENOIDS, SPRING CENTRED "C" MOUNTING

Spool type		Covering	Transient position
01		+	
02		-	
03		+	
04*		-	
44*		-	
05		+	
66		+	
06		+	
07*		+	
08*		+	
09*		+	
10*		+	
22*		+	
11*		+	
12*		+	
13*		+	
14*		-	
28*		-	

ONE SOLENOID, SIDE A "E" MOUNTING

Spool type		Covering	Transient position
01		+	
02		-	
03		+	
04*		-	
44*		-	
05		+	
66		+	
06		+	
08*		+	
10*		+	
12*		+	
15		-	
16		+	
17		+	
14*		-	
28*		-	

**DIRECTIONAL CONTROL VALVES
STANDARD SPOOLS CETOP 3/NG6**

NOTE

(*) Spool with price increasing

• With spools 15 / 16 / 17 only mounting E / F are possible

• 16 / 19 / 20 / 21 spool not planned for AD3E...J*

• For lever operated the spools used are different.
Available spools for this kind of valve see AD3L..

ONE SOLENOID, SIDE B "F" MOUNTING


Spool type		Covering	Transient position
01		+	
02		-	
03		+	
04*		-	
44*		-	
05		+	
66		+	
06		+	
08*		+	
09*		+	
10*		+	
22*		+	
12*		+	
13*		+	
07*		+	
15		-	
16		+	
17		+	
14*		-	
28*		-	

TWO SOLENOIDS "D" MOUNTING

Spool type		Covering	Transient position
19*		-	
20*		+	
21*		+	

AD3E... DIRECTIONAL CONTROL VALVES SOLENOID OPERATED CETOP 3/NG6

1




A max. counter-pressure of 8 bar at T is permitted for the variant with a microswitch (M1).
 (1) DC: Dynamic pressure allowed on P for 1 million of cycles.
 (2) DC: Dynamic pressure allowed for 2 millions of cycles.
 AC: Dynamic pressure allowed for 350.000 of cycles.
 For dynamic pressure of 100 bar are allowed 1 million cycles.

Max. pressure port P/A/B (1)	350 bar
Max. pressure port T (for DC) (2)	250 bar
Max. pressure port T (for AC) (2)	160 bar
Max. flow	80 l/min
Max. excitation frequency	3 Hz
Duty cycle	100% ED
Fluid viscosity	10 ÷ 500 mm ² /s
Fluid temperature	-25°C ÷ 75°C
Ambient temperature	-25°C ÷ 60°C
Max. contamination level	class 10 in accordance with NAS 1638 with filter $\beta_{25} \geq 75$
Weight with one DC solenoid	1,65 Kg
Weight with two DC solenoids	2 Kg
Weight with one AC solenoid	1,31 Kg
Weight with two AC solenoids	1,72 Kg

CALIBRATED DIAPHRAGMS (3)	
Ø mm	Code
blind	M52.05.0023/4
0.5	M52.05.0023/1
0.6	M52.05.0023/6
0.7	M52.05.0023/8
0.8	M52.05.0023
1.0	M52.05.0023/2
1.2	M52.05.0023/3
1.5	M52.05.0023/7
2.0	M52.05.0023/10
2.2	M52.05.0023/9
2.5	M52.05.0023/5

(3) For high differential pressure please contact our technical department.

OVERALL DIMENSIONS




LIMITS OF USE (MOUNTING C-E-F)

The tests have been carried out with solenoids at operating temperature and a voltage 10% less than rated voltage with a fluid temperature of 40°C. The fluid used was a mineral oil with a viscosity of 46 mm²/s at 40°C. The values in the diagram refers to tests carried out with the oil flow in two directions simultaneously T = 2 bar (e.g. from P to A and the same time B to T). In the case where valves 4/2 and 4/3 were used with the flow in one direction only, the limits of use could have variations which may even be negative. Rest times: the values are indicative and depend on following parameters: hydraulic circuit, fluid used and variations in hydraulic scales (pressure P, flow Q, temperature T). The limit of use for AC solenoids were detected with 50 Hz power.

Direct current:	Energizing	30 ÷ 50 ms.	Alternating current:	Energizing	8 ÷ 30 ms.
	De-energizing	10 ÷ 30 ms.		De-energizing	15 ÷ 55 ms.

NOTE: The operating limits shown are valid for mountings C, E, F.


DIRECT CURRENT SOLENOIDS (DC)



Spool type	Solenoids	
	DC	AC
01	1	9
02	1	9
03	3	10
04	2	15
44	1	9
05	1	16
06-66	5	13
11-22	4	17
14-28	7	12
15	8	14
16	6	11

Curves

ALTERNATING CURRENT SOLENOIDS (AC)



AD3E...J* VALVES WITH SPOOL MOVEMENT SPEED CONTROL VARIANT J*

Valves type AD3E...J* with spool movement speed control

1

These ON-OFF type valves used a lower spool movement speed than usual for conventional solenoid valves is required to prevent impacts which could adversely affect the smooth running of the system. The system consist of reducing the transfer section for the fluid from one solenoid to the other by means of calibrated orifices.

- This version can only be used with a direct current (DC) and also involves a **reduction in the limits of use so that we suggest to always test the valve in your application**

- To order AD3...J* version valves, specify the orifices code.

- The operation is linked to a minimum counter-pressure on T line (1 bar min.)

- The switching time referred to the spool travel detected by a LVDT transducer can vary for the NG6 valve from a minimum of 100 to a maximum of 300 ms depending on 5 fundamental variables:

- 1) Diameter of the calibrated orifices (see table)
- 2) Hydraulic power for clearance referring to flow and pressure values through valve
- 3) Spool type
- 4) Oil viscosity and temperature
- 5) Counter-pressure at T line

Max. pressure ports P/A/B	320 bar
Max. pressure port T (*)	250 bar
Max. flow	30 l/min
Max. excitation frequency	2 Hz
Duty cycle	100% ED
Fluid viscosity	10 ÷ 500 mm ² /s
Fluid temperature	-25°C ÷ 75°C
Ambient temperature	-25°C ÷ 60°C
Weight with one DC solenoid	1,65 Kg
Weight with two solenoids DC solenoids	2 Kg


(*) Pressure dynamic allowed for 2 millions of cycles.

CALIBRATED ORIFICES AVAILABLE		
ø (mm)	M4x4	Code
0.3	M89.10.0028	3S (J3+S1)*
0.4	M89.10.0029	JS (J4+S1)*
0.5	M89.10.0006	5S (J5+S1)*
0.6	M89.10.0030	6S (J6+S1)*

* Old code

- Possible mountings: C / E / F / G / H
- 16 / 19 / 20 / 21 spools not planned for AD3E...J*

OVERALL DIMENSIONS



AD3E...KJ / 7J HIGH CORROSION RESISTANCE


1



AD3EJ..	
"D15" DC COILS	CAP. I • 19
STANDARD CONNECTORS	CAP. I • 20

- This variant has a Zinc-Nickel surface treatment on metallic parts for a higher corrosion resistance
- Coil windings are sealed and outer metal housing has eCoat surface treatment
- The complete valve withstand more than 700 hours exposure of Salt Spray Test (test performer according to UNI EN ISO 9227 and evaluation according to UNI EN ISO10289).
- The plastic blind retainer is assembled as standard to protect the end surface of solenoid tube

OVERALL DIMENSIONS





AD3V...	
"D15" DC COILS	CAP. I • 19
STANDARD CONNECTORS	CAP. I • 20
LVDT	CAP. I • 22

AD3V... CETOP 3/NG6 WITH PROXIMITY SENSOR LVDT

The single solenoid directional valves type AD.3.V are used in applications where the monitoring of the position of the spool inside the valve is requested to manage the machine safety cycles in accordance with the accident prevention legislation. These directional valves are equipped with an horizontal positioned inductive sensor on the opposite side of the solenoid, which is capable of providing the first movement of the valve when the passage of a minimum flow is allowed. Integrated in safety systems, these valves intercept actuator movements that could be dangerous for the operators and for the machine.

Max. operating pressure ports P/A/B (*)	350 bar
Max. operating pressure port T dynamic (**)	250 bar
Max. flow	60 l/min
Max. excitation frequency	3 Hz
Duty cycle	100% ED
Fluid viscosity	10 ÷ 500 mm ² /s
Fluid temperature	-25°C ÷ 75°C
Ambient temperature	-25°C ÷ 60°C
Type of protection (in relation to connector used)	IP 66
Weight	1,7 Kg

(*) Dynamic pressure allowed on P for 800.000 cycles.
(**) Pressure dynamic allowed for 2 millions of cycles.


- Possible mountings: E / F / H
- The valve is supplied with DC solenoid only

ORDERING CODE

AD	Directional control valve
3	CETOP 3/NG6
V	Directional valve with single solenoid and LVDT proximity sensor
***	Spool and mounting (table 1)
*	Voltage (table 2)
**	Variants (table 3)
3	Serial No.

CE registered mark for industrial environment with reference to the electromagnetic compatibility. European norms:
- EN50082-2 general safety norm - industrial environment
- EN 50081-1 emission general norm - residential environment

PRESSURE DROPS



Spool type	Connections				
	P→A	P→B	A→T	B→T	P→T
01	5	5	5	5	
02	6	6	6	6	5
06	5	5	6	5	
16	5	5	4	4	
17	1	3			
66	5	5	5	6	
32	1	1	2	2	

Curves No.

The diagram at side shows the Δp curves for spool in normal usage. The fluid used is a mineral oil with a viscosity of 46 mm²/s at 40°C; the tests have been carried out at a fluid temperature of 40°C.

TAB.2 - VOLTAGE

D15 COIL (30W) **	
L	12V
M	24V
V	28V*
N	48V*
Z	102V*
P	110V*
R	205V*
W	Without DC coils and connectors

115Vac/50Hz
120Vac/60Hz with rectifier

230Vac/50Hz
240Vac/60Hz with rectifier

Voltage codes are not stamped on the plate, they are readable on the coils.

* Special voltage
** Technical data see Cap. I • 19

TAB1 - STANDARD SPOOLS FOR AD3V

POSSIBLE MOUNTING: E / F / H			
Spool type	Covering	Transient position	
01E	+		
01F	+		
02E	-		
06H*	+		
16E	+		
17F	+		
66F	+		
32E	+		


(*) Spool with price increasing

TAB.3 - VARIANTS

No variant (without connectors)	S1(*)
Viton	SV(*)
Emergency button	ES(*)
Without proximity connector LVDT	S3
Without coils and proximity connector	S4
AMP Junior coil	AJ(*)
AMP Junior coil and integrated diode	AD(*)
Coil with flying leads (175mm)	SL
Deutsch DT04-2P Coil type	CZ

Other variants available on request.

(*) Coils with Hirschmann and AMP Junior connection supplied without connectors. The connectors can be ordered separately, Cap. I • 20.



AD3L... LEVER OPERATED CETOP 3/NG6



Max. pressure ports P/A/B	320 bar
Max. pressure port T	160 bar
Max. flow	60 l/min
Lever angle	2 x 17°
Fluid viscosity	10 ÷ 500 mm ² /s
Fluid temperature	-25°C ÷ 75°C
Ambient temperature	-25°C ÷ 60°C
Max. contamination level	class 10 in accordance with NAS 1638 with filter $\beta_{25} \geq 75$
Weight	1,2 Kg
Weight M1 variant	1,8 Kg

AD3L...

STANDARD SPOOLS

CAP. I • 10


ORDERING CODE

AD	Directional valve
3	CETOP 3/NG6
L	Lever operation
**	Spool type (see table 1) Spool symbol see CAP. I • 10
*	Mounting type (see table 2)
*	Z = Valve with lever X = Valve without lever
*	Variants (see table 3)
4	Serial No.

TABLE 1 - SPOOLS TYPE

• Available spools:
01 / 02 / 03 / 04 / 05 / 06 / 66
13 / 15 / 16 / 17

TABLE 2 - MOUNTING TYPE



(1) For spools 15-16-17 the lever is mounted on site B

OVERALL DIMENSIONS




TABLE 3 - VARIANTS TABLE

VARIANTS	CODE (♦)
No variant	00
Viton	V1
Preset for microswitch Microswitch type MK code 1319098 can be ordered separately.	M1 (♦)
With detent (*) (mechanical connection) (Springs are different from those for standard versions)	D1 (♦)
Preset for microswitch + Detent (*)	MD (♦)
Lever length 162 mm	L1
Lever length 192 mm	L2
♦ Variant codes stamped on the plate	
(*) max. 150.000 cycles.	

DIRECTIONAL CONTROL VALVES OTHER OPERATOR CETOP 3/NG6

INTRODUCTION

The directional control valves NG6 are designed for subplate mounting with an interface in accordance with UNI ISO 4401 - 03 - 02 - 0 - 94 standard (ex CETOP R 35 H 4.2-4-03), and can be used in all fields on account of their high flow rate and pressure capacities combined with compact overall dimensions.

The use of solenoids with wet armatures allows a very practical, safe construction completely dispensing with dynamic seals; the solenoid tube is screwed directly onto the valve chest whilst the coil is kept in position by means of a lock nut.

The special, precise construction of the ports and the improvement of the spools enables relatively high flow rates to be accommodated with a minimal pressure drop (Δp).

The centre position is obtained by means of calibrated length springs which reposition the spool in the centre or end of travel position once the action of the impulse is over.

The valves are designed for use with DIN 51524 standard hydraulic mineral oils and it is recommended that filters should be fitted to ensure a maximum contamination level of class 10 in accordance with NAS 1638, $B_{25} \geq 75$.

ALTRI COMANDI

STANDARD SPOOLS	CAP. I • 10
AD3P...	CAP. I • 17
AD3O...	CAP. I • 17
AD3M...	CAP. I • 18
AD3D...	CAP. I • 18

ORDERING CODE

AD	Directional valve
3	CETOP 3/NG06
*	Type of operator P = Pneumatic O = Oleodynamic M = Mechanically D = Direct mechanically (For other operator see past pages)
**	Spool (see CAP. I • 10)
*	Mounting type (tab.1)
Z	No voltage
**	Variants: 00 = no variant V1 = Viton H1 = Marine version (for AD3P only) DI(*) = Internal draining (for AD3O only)
2	Serial No.


TAB.1 MOUNTING

STANDARD	
C	
D	
E	
F	
SPECIALS (WITH PRICE INCREASING)	
G	
H	
I	
L	
M	

• In case of **mounting D** with detent a maximum supply time of 2 sec is needed (only for AC coils).

(*)The DI variant is recommended in the environments characterised by the presence of dust or any type of contamination.

PRESSURE DROPS



Spool type	Connections				
	P→A	P→B	A→T	B→T	P→T
01	5	5	5	5	
02	6	6	6	6	5
03	5	5	6	6	
04	1	1	2	2	4
05	5	5	5	5	
06	5	5	6	5	
66	5	5	5	6	
07		4	6		
08	6	6			
09		5		5	
10	5	5	5	5	

Curve No.

Spool type	Connections				
	P→A	P→B	A→T	B→T	P→T
11	4			6	
22		4	6		
12		5	6	6	
13		5	6	6	
14	2	1	1	1	2
28	1	2	1	1	2
15 - 19	4	4	6	6	
16	5	5	4	4	
17 - 21	1	3			
18	5	5			
20	4	4	4	4	

Curve No.


The diagram at the side shows the pressure drop curves for spools during normal usage. The fluid used is a mineral oil with a viscosity of 46 mm²/s at 40°C; the tests have been carried out at a fluid temperature of 40°C. For higher flow rates than those in the diagram, the losses will be those expressed by the following formula:

$$\Delta p_1 = \Delta p \times (Q_1/Q)^2$$

where Δp will be the value for the losses for a specific flow rate Q which can be obtained from the diagram, Δp_1 will be the value of the losses for the flow rate Q₁ that is used.

AD3M... MECHANICALLY OPERATED TYPE VALVES CETOP 3/NG6

1



Max. pressure ports P/A/B	320 bar
Max. pressure port T	160 bar
Max. flow	60 l/min
Minimum operating force - see note (*)	2,5 Kg
Maximum operating force - see note (**)	13 Kg
Cam angle	27°
Fluid viscosity	10 ÷ 500 mm ² /s
Fluid temperature	-25°C ÷ 75°C
Ambient temperature	-25°C ÷ 60°C
Max. contamination level	class 10 in accordance with NAS 1638 with filter $\beta_{25} \geq 75$
Weight	1 Kg

• Possible mountings:
E / F / G / H


• Ordering code see page before

• Note:

(*) In the absence of counter-pressure at port T

(**) with a pressure of 160 bar at port T


OVERALL DIMENSIONS



Stroke	12,4 mm
Working stroke	3 mm

Fixing screws UNI 5931 M5x30
with material specifications min. 8.8
Tightening torque 5 Nm / 0.5 Kg

Support plane specifications



EAD3M - 02/2000/e

AD3D... DIRECT MECHANICALLY OPERATED TYPE VALVES CETOP 3/NG6



Max. pressure ports P/A/B	320 bar
Max. pressure port T	20 bar
Max. flow	60 l/min
Operating force - see note (*)	6 Kg
Fluid viscosity	10 ÷ 500 mm ² /s
Fluid temperature	0°C ÷ 75°C
Ambient temperature	-25°C ÷ 60°C
Max. contamination level	class 10 in accordance with NAS 1638 with filter $\beta_{25} \geq 75$
Weight	1,5 Kg


• Possible mountings:
E / F / G / H

• Ordering code see page before

• Note:

(*) In absence of counter-pressure at port T


OVERALL DIMENSIONS




Stroke	6 mm
Extra stroke	2 mm
Working stroke	3 mm

Fixing screws UNI 5931 M5x30
with material specifications min. 8.8
Tightening torque 5 Nm / 0.5 Kg

Support plane specifications



EAD3D - 02/2000/e



"D15" DC COILS FOR CETOP 3

Type of protection (in relation to the connector used)	IP 66
Number of cycles	18.000/h
Supply tolerance	±10%
Ambient temperature	-25°C ÷ 60°C
Duty cycle	100% ED
Insulation class wire	H
Weight	0,354 Kg



- AMP Junior coils (with or without diode) and coils with flying leads and coils type Deutsch, are available in 12V or 24V DC voltage only.
- The pastic type coil (RS variant) is available in 12V, 24V, 28V or 110V DC voltage only.

1

VOLTAGE (V)	MAX WINDING TEMPERATURE (AMBIENT TEMPERATURE 25°C)	RATED POWER (W)	RESISTANCE AT 20°C (OHM) ±10%
12V	110°C	30	4.8
24V	110°C	30	18.8
28V*	110°C	30	25.6
48V*	110°C	30	75.2
102V(**)	110°C	30	340
110V(**)	110°C	30	387
205V(**)	110°C	30	1375

* Special voltages

** The european low voltage directive is applied to electrical equipments used at a nominal voltages between 50 and 1000 VAC or 75 and 1500 VDC. In conformity with the low directive each part of the manifold or the subplate on which the valve is mounted should be connected to a protective earth with a resistance less than 0.1 ohms.




"B14" AC SOLENOIDS FOR CETOP 3

Type of protection (in relation to the connector used)	IP 65
Number of cycles	18.000/h
Supply tolerance	+10% / -10%
Ambient temperature	-30°C ÷ 60°C
Duty cycle	100% ED
Insulation class wire	H
Weight	0,436 Kg


VOLTAGE (V)	MAX. WINDING TEMPERATURE (AMBIENT TEMPERATURE 25°C)	RESISTANCE AT 20°C (OHM) ±10%	RATED POWER. (VA)	PICKUP CURRENT (A)
24V/50Hz - 24V/60Hz	100°C - 96°C	1.7	54 - 40	5.6 - 5
48V/50Hz - 48V/60Hz	112°C - 98°C	6.8	45 - 34	5.3 - 5
115V/50Hz - 120V/60Hz *	133°C - 101°C	32.5	61 - 51	3.2 - 3.2
230V/50Hz - 240V/60Hz *	120°C - 103°C	134	62 - 52	1.6 - 1.6

* The european low voltage directive is applied to electrical equipments used at a nominal voltages between 50 and 1000 VAC or 75 and 1500 VDC. In conformity with the low directive each part of the manifold or the subplate on which the valve is mounted should be connected to a protective earth with a resistance less than 0.1 ohms.



CONNECTORS DIRECTIONAL CONTROL VALVES IN ACCORDANCE WITH DIN 43650/ISO4400

1



Connector	Protection level	Type	Cable gland	Code
Standard	IP65	Black color	PG09	V86 05 0002
		Grey color	PG09	V86 05 0004
		Black color	PG11	V86 05 0006
		Grey color	PG11	V86 05 0008
Lens cover with pilot light (bipolar led) (*)	IP65	12 VAC/VDC	PG09	V86 10 0018
		24 VAC/VDC	PG09	V86 10 0012
		115 VAC/VDC	PG09	V86 10 0020
		230 VAC/VDC	PG09	V86 10 0022


(*) Don't use for proportional versions

Connector	Protection level	Type	Cable gland	Code
With rectifier (*) Inlet voltage 12÷230 VAC Outlet voltage 9÷205 VDC	IP65	Black color	PG09	V86 20 0002
		Grey color	PG09	V86 20 0004
Lens cover with pilot light (bipolar led) and rectifier (*) Inlet voltage 12÷230 VAC Outlet voltage 9÷205 VDC	IP65	12 VAC	PG09	V86 25 0018
		24 VAC	PG09	V86 25 0019
		48 VAC	PG09	V86 25 0020
		115 VAC	PG09	V86 25 0021
		230 VAC	PG09	V86 25 0022


(*) Don't use for proportional versions

Connector	Protection level	Type	Cable gland	Code
With protection level IP67	IP67	Black color	—	V86 28 0001
		Grey color	—	V86 28 0002

Electrical circuits




ELECTRICAL FEATURES OF CONNECTORS




Description	IP65	IP67
AC rated voltage	Max. 250 V	Max. 250 V
DC rated voltage	Max. 300 V	Max. 300 V
Pin contact nominal current	10A	10A
Pin contact max. current	16A	16A
Max. section cable	1.5 mm ²	1.5 mm ²
Cable gland PG09 - M16x1,5	Ø cable 6 ÷ 8 mm	Ø cable 4 ÷ 7 mm
Cable gland PG11 - G 1/2" - M20x1,5	Ø cable 8 ÷ 10 mm	—
Protection level	IP65 EN60529	IP67 EN60529
Insulation class	VDE 0110-1/89	VDE 0110-1/89
Operating temperature	-40°C ÷ 90°C	-20°C ÷ 80°C

The degrees of protection indicate is guaranteed only if the connectors were properly mounted with his original seals.

AMP JUNIOR CONNECTORS



Connector	Type	Cable section	Pin contact max current	Code
AMP Junior connector Timer 2 contact	Black color	0,5 ÷ 1,5 mm ²	10A	RKRC080800



VARIANTS (*) - EMERGENCY CONTROL LEVER FOR DIRECTIONAL CONTROL VALVES (ADC/AD3E)

The emergency control lever for solenoid valves, represents a develop in terms of safety and flexibility among applied hydraulic components.

Thanks to his flexibility, the component was designed to be inserted between the valve body and the spool, providing total interchangeability between the different types of solenoid body valves. It is compatible with the standard CETOP 3 and stackable valves with threaded connections –G3/8” or 9/16-18UNF (SAE 6). The component is available for both directional control and proportional valves (for the last type of control please contact our Technical Department) As an emergency lever applied to solenoid valves, the control can be used as a safety device in conformity with the industry standards , also playing an useful role in the event of power cuts. The control can be used in agricultural and mobile fields; the manual action can be used to carry out periodic maintenance work on mobile components of the vehicle , in perfectly safe working conditions.

(*) VARIANTS

Variant	Description
LE	Standard coil with Hirschmann connection or without coil (W voltage)
LF	Standard coil without Hirschmann connection(*)
AX	AMP Junior coil(*)
CE	Deutsch coil

Other variants available on request.


(*) Coils with Hirschmann and AMP Junior connection supplied without connectors. The connectors can be ordered separately, Cap. I • 20.

Max operating pressure port T:	
dynamic	160 bar
static	210 bar
Max operating pressure port P for series connection configuration	160 bar

- MOUNTING TYPE: C / F / H
- SPOOLS TYPE: 01/02/03*/04/16/17/66

* The spool 03 is allowed only on AD3E. Not permitted with ADC3


HYDRAULIC SIMBOL



MOUNTING COMPATIBILITY

CODE VALVE	DESCRIPTION	COIL	VOLTAGE
ADC3...	Directional control valve	A09	27 W
AD3E...	Directional control valve	D15	30 W

OVERALL DIMENSION




PROXIMITY SENSOR TYPE LVDT

Supply voltage	20..32 VDC
Polarity reversal protection	yes
Switching point hysteresis	≤ 0,05 mm
Reproducibility	± 0,02 mm
Max. output current	≤ 400 mA; duty ratio 100%
Protection against short circuit	yes
Operating temperature	-25°C ÷ 80°C
Connection type	connector
Protection according to DIN	IP65
Max. pressure	400 bar

CE certificate according to 89/336/EEC EMC is provided. A screened cable is needed.


The LVDT position transducers allow to check exactly the very instant when the passage of a minimum flow is allowed.

FUNCTIONAL DIAGRAM ON PIN 2 AND 4




0 = Voltage Pin 2 and Pin 4 < 1,8 V
1 = Voltage Pin 2 and Pin 4 20..32 VDC

OVERALL DIMENSION LVDT



OVERALL DIMENSIONS CONNECTOR





Type of protection IP67
Ambient temperature -40°C ÷ 85°C

Ordering code: V86400003

ELECTRICAL CONNECTIONS LVDT



A

With this connection, on the **Pin 2** an **output signal** is active when no oil is crossing the valve (from P → B).



B

With this connection, on the **Pin 2** there is **no output signal** when oil is crossing the valve (from P → B).



NB: connecting the output to Pin 4 or Pin 2 the type of contact, normally closed or open, can be chosen.